

Request for Quotation - Technical Assessment

Please Note: A quotation cannot be issued unless all of the information requested in this document is submitted. Changes can be made at any time, but will require an additional quotation.



The smart choice for hazardous areas
Mohib Jamal | 44 7963 518577
<mohib.jamal@atexengineering.co.uk>

End User Site Details

Registered
Company Name

Site Address

Site Contact

Equipment Details

Truck Make and Model

Qty

Capacity (kg)

Cab Fitted

Note: The Truck wiring Diagram is required on all trucks prior to delivery to ATEX Engineering

Area Classification

Gas Hazard

Temperature Class

Gas Group

2G (Zone 1) Gas

T3 (200°C)

IIA

3G (Zone 2) Gas

T4 (135°C)

IIB

Added Safety Only

Other
Details

Other
Details

List of Gases

OR

Dust Hazard

2D (Zone 21) Dust

Combustible Dust (IIB)

Cloud Ignition Temperature (°C) Dust

3D (Zone 22) Dust

Combustible Dust (IIIC)

Layer Ignition Temperature (°C)

Dust Materials

Application

Operation

Ambient Temperature Range - 20° to +40°C

Inside

Other please specify (°C)

Outside

Environmental Conditions

Very Clean

Clean

Dirty

Very Dirty

Extreme Gradients

Height Restrictions - (i.e. Doorways, Overhead Pipes etc)

If Yes, please
specify

Electric Vehicles

Traction Motor	AC	DC	Qty
Hydraulic Motor	AC	DC	
Battery	Voltage		Capacity (Ah)



The smart choice for hazardous areas
Mohib Jamal | 44 7963 518577
<mohib.jamal@atexengineering.co.uk>

Accessories

- Any accessories or additional devices need to be specified to enable an accurate quote to be provided. The siting of these is subject to review by ATEX Engineering on receipt of the equipment.
- All accessories listed shall arrive fitted to the truck for ATEX Engineering to assess.
- Accessories supplied which are not specified will be removed and returned.

Forks	Qty	Class	Front Combi Lights (marker, indicator)
Working Lights (Qty)	Front	Rear	Rear Combi Lights (marker, indicator)
Blue Spot Light (Qty)	Front	Rear	Flashing Beacon & Audible Reverse
Front Wiper	Electric	Manual	Cab Heater
Rear Wiper	Manual		

Additional/Other Equipment or Notes

Additional Information

- EN1755:2015 requires that all machines that travel over 6km/h be fitted with anti-static tyres. Not all OEM's supply anti-static tyres and this could affect the lead time.

Speed Restriction to 6km/h

Unable to Restrict Speed (anti-static tyres are required)

The equipment offered will be in accordance with the Essential Health and Safety requirements of the ATEX Directive 2014/34/EU.

The operations manager or on-site safety officer at the end user site should confirm that the selected equipment is suitable for the stated area classification and is correct for their specific application.

Customer Approval

We confirm that the information provided within is correct and understand the specification of the equipment is our sole responsibility. We also recognise that any work will not commence until this document has been fully completed and returned.

Name Email

Company Phone

Date Signature